Brother Titan Industrial Printer Series

4-inch Industrial Barcode & Label Printers





Print ultra-fast. Again. And again. And again.


Introducing the new line of 4 inch industrial printers: **Brother Titan Industrial Printer** series. These compact high volume label printers deliver the quality barcode labels you need with the support you want.

The **Brother Titan Industrial Printer** produces consistently crisp barcode labels at top speeds. Push the boundaries of what you can accomplish with refreshingly easy designed to drop-in integration and a complete set of connectivity choices. Experience it all with some of the most affordable price points and subscription¹ options available. Then, discover unmatched support that's "at your side" for life.

These industrial printers are ideally suited for harsh conditions and longterm use in warehouses, manufacturing and across the supply chain.

- **Performance:** Produce quality, scannable barcodes at up to 10ips, you can also scale up to 300dpi for visibly sharpresolutions.
- **Support:** Backed with an industry leading 2-year Premier Limited Warranty, even includes the printhead², and responsive, lifetime³ customer support.
- **Integration:** Seamlessly integrate with YOUR system using a full suite of included emulations, SDKs, and drivers.
- **Versatile Connectivity:** All models come standard with Ethernet/LAN, USB 2.0, Host-USB and RS232C Serial, plus options to add a Wi-Fi® module.
- Buy or Subscribe: Upfront affordability with some of the lowest price points in the industry or subscription¹ options for one low monthly fee.
- **Useability:** See printer status and make selections on the fly with a 3.5-inch, full-color HVGA touch panel display.

Tools and Software for Easy Integration



















¹ Shift & Print Subscription Service is subject to credit approval.

 $^{^2\,\}mbox{Up}$ to 1 million inches. For full details contact your Brother Sales Representative or visit brothermobilesolutions.com/warranty.

³ For the life of the product.

Technical Specifications for the TJ4021TN and TJ4121TN		
Base Model	TJ4021TN	TJ4121TN
Printing Technology	Thermal Transfer, Direct Thermal	
Media/Print Width	4.7" (120mm) / 4.21" (107mm)	4.7" (120mm) / 4.16" (105.7mm)
Print Head Resolution	203dpi x 203dpi (8 dots/mm)	300dpi x 300dpi (12 dots/mm)
Print Engine Speed	Up to 10ips (254mm/sec)	Up to 7ips (177.8mm/sec)
In Box Solution	Seagull BarTender UltraLite Design/Print Software Application, Brother Printer Management Software Tool	
OS Supported	Windows Server 2019/2016/2012 R2/2012, Windows 10/8.1/7 (64-bit and 32-bit), Mac® OS X® 10.11.x, macOS® 10.12.x or Higher, Linux	
SDK Support	Windows Server 2019/2016/2012 R2/2012/2008 R2/2008, Windows 10/8.1/8/7, Windows Vista, Windows 10/8.1/7, Android™ v5.0 or Later, iOS v9.0 or Later	
Printer Languages	FBPL, ZPL II®, EPL2, DPL	
Control Panel	6 Keys/ 1 Status LED (3 Color), 3.5" HVGA Color Touch Screen Control Panel	
Standard Interfaces	Ethernet LAN (10/100Base-TX), USB 2.0, Host-USB, RS232C	
Optional Interfaces	Wi-Fi® WLAN (5GHz 802.11a/n and 2.4GHz 802.11b/g/n Infrastructure)	
Security Protocols	WLAN 802.11i, 802.1x WPA2-Enterprise (EAP-FAST, EAP-TTLS, EAP-TLS, PEAPv0)	
Wireless Security	WEP 64/128bit, WPA-PSK/WPA2 (TKIP/AES)	
Bluetooth Profiles	No Bluetooth Option	
Printer Memory	128MB Flash, 128 SDRAM	
Resident Barcodes	Linear: Code39, Code93, Code128, ITF, UPC-A/E, EAN8/13, GS1-128 (UCC/EAN-128), MSI/Plessey, Standard 2of5 (IATA), Industrial 2of5, Codabar (NW-7), ITF14, EAN14, POSTNET, LOGMARS, Code11, TELEPEN, PLANET, Deutsche Post Identcode, Deutsche Post Leitcode, China Post 2 Dimensional: PDF417/MicroPDF417, Data Matrix, Maxicode, QR Code, Aztec, GS1 DataBar (RSS), CODABLOCK F, Code49, TLC 39	
Real Time Clock	Standard	
Label Peeler	Optional with Rewinder (PA-LP-005)	
Automatic Cutter	Optional Guillotine Full Cutter (PA-CU-004)	
Audio Device	Standard	
Printer Sensors	Full Width Moveable Gap (Transmissive) and Black Mark (Reflective), Ribbon Encoder and Ribbon End, Head Open Peeler (Optional)	
Media Type	Roll or Fan-Fold / Die Cut or Continuous / Label and Tag	
Media Roll Size	8.00" (203.2mm) Outer Diameter, Wound Out, 1" (25.4mm) or 3" (76.2mm) Core Inside Diameter	
Media Loading	Internal: 1" Spindle with 3" Core Adapters (2 pieces), External: Rear Feed (External Roll or Fanfold)	
Media Specifications	Width (Tear, Peeler): 0.79" - 4.72" (20mm - 120mm), Length (Peeler): 1" – 4.72" (25.4mm – 120mm) Width (Cutter): 0.79" – 4.49" (20mm – 114mm), Length (Tear, Cutter, 203dpi): 0.2" – 1,000" (5mm – 25,400mm), Length (Tear, Cutter, 300dpi): 0.2" – 450" (5mm – 11,430mm), Thickness: 2.36mil – 11mil (0.06mm - 0.28mm)	
Ribbon Types	Wax, Semi (Wax/Resin), Resin	
Ribbon Length	1,476' (450m) Length / 3.2" (81.3mm) OD or 984' (300m) Leng	th / 2.64' (67mm) OD, Wound In/Out on 1" (25.4mm) Core ID (No Notch Required)
Ribbon Width	4.33"	(110mm) – 1.57" (40mm)
Ribbon Take Up Core	4.33" (110mm) Widt	h / 1" (25.4mm) ID (No Notch Required)
Optional Accessories	Wi-Fi Interface (PA-WI-002), Label Peeler with Liner Rewinder (PA-LP-005), Automatic Cutter (PA-CU-004), 203dpi Print Head (TBD), 300dpi Print Head (TBD), Platen Roller (TBD)	
Carton Contents	Printer, Power Cord, USB Cable, Ribbon Take-Up Core, 3" Media Supply Core Adapter (2 pieces), Documentation	
Printer Size (w x h x l) /Weight	9.76" x 10.79" x 17.17" (248mm x 274mm x 436mm) / 20.7 lbs. (9.4 kg)	
Power Specifications	100 - 240VAC 50/60Hz 2.0A	
ENERGY STAR Certified	Energy Star 3.0	
Operating Temperature/Humidity	32°F - 104°F (0°C - 40°C) / 25% - 85% non-condensing	
Storage Temperature/Humidity	1005 11005 / 1005	C - 60°C) / 10% - 90% non-condensing

Brother Titan Industrial Printer Supplies, Accessories and Services



Supplies

- Brother Premium labels rolls and ink ribbon types for all your applications.
- Custom options also available.



Accessories

• We offer optional print heads, platen rollers, peeler, cutter and Wi-Fi interface.



Extended Warranty Service

• Extend the useful life of your printer by adding an extended service program.



